

Jowat Adhesives Pellets & Cartridges



**Quality glue in pellets and cartridges.
For use in Automatic Edgebanders**

Descriptions:

Pellets

- J23700:** Polyolefin based hot melt formulated to resist discoloration in the melt reducing hassle and cost of glue pot maintenance.
- J28140:** Solid wood, veneer, PVC and resinated paper edgebands. Excellent thermal stability, string free.
- J28220:** Contour edgebanding - PVC, paper, polyester. Low temp applicaton.
- J28860:** For edgebanding veneer, solid wood, resin impregnated paper edgebands, PVC, ABS and primed* HPL. Can also be used for precoating and softforming applications.
- J28870:** Economical, versatile hot melt which runs on all edgebanders. Long open time, excellent trimming properties, good adhesion performance at low temperatures. May also be used for precoating and soft forming applications
- J29630:** Edgebanding - veneer, resin impregnated paper edgebands, PVC and similar.
- J28030:** Solid wood, veneer, PVC and resinated paper edgebands. Also for softforming (especially designed for BAZ machines). Translucent glue line.
- J28090:** High viscosity hot melt for solid wood, veneer, PVC and resinated papers. Also for softforming. Clear melt.
- J26600:** For assembly applications in the furniture, electrical and metal industries. Good adhesion to difficult to adhere to surfaces (lacquered, polyester, PVC and finished paper foils).

Cartridges

- J28680:** Medium-high viscosity cartridge suitable for primed HPL, solid wood, veneer, PVC and resinated paper edgebands..
- J28630:** Unfilled cartridge, medium viscosity with high heat resistance. For automatic edgebanding, suitable for solid wood, veneer, PVC, HPL and resinated paper edgebands.

Primer

- J14860:** When used as a primer, this adhesive should be diluted with water 50:50. Due to the differences in HPL, Jowat strongly recommends to carry out suitability tests prior to production.

Filled Glues

- For use with PVC, wood and high pressure laminate
- Good running properties
- Excellent wettability
- Very good adhesion
- High bond strength
- Good heat resistance

	Qty/lbs.	Color	*HPL	*PVC	Wood	Other
Pellets						
J23700 44	44	light beige	•	•	•	veneer
J26600	33					assembly glue
J28140 44	44	beige		•	•	veneer
J28220 44	44	natural		•		contour banding
J28860 44	44	natural	•	•	•	veneer
J28861 44	44	white	•	•	•	
J28870 44	44		•	•	•	veneer
J29630 44	44	natural		•	•	veneer
J29631 44	44	white		•	•	

Cartridges (48 per box unless otherwise noted)

J28680	35	natural	•	•	•	veneer
J28680 6						6 pack of cartridges
J28681	35	white	•	•	•	veneer
J28681 6						6 pack of cartridges
J28682	35	brown	•	•	•	veneer
J28682 6						6 pack of cartridges
J28683	35	black	•	•	•	veneer
J28683 6						6 pack of cartridges

Unfilled Glues

- Cleaner running; glue pot stays cleaner longer
- Used on a wider variety of substrates
- Good coverage
- Transparent

	Qty/lbs.	Color	*HPL	*PVC	Wood	Other
Pellets						
J28030 44	44	natural		•	•	veneer
J28090 44	44	clear		•	•	veneer
Cartridges						
J28630	26	natural	•	•	•	veneer

Primer

J14860 Gallon

*HPL- high pressure laminate *PVC- poly vinyl chlorate